


PRODUCT DETAILS

Eoptolink's 100G CWDM 2km QSFP28 Optical Transceiver



EOLQ-161HG-O-02-X6 Series

Single-Mode, 100G QSFP28
With LC interface



Product Description

Eoptolink's CWDM Single Lambda QSFP28 transceiver module is designed for use in 100 Gigabit Ethernet links over 2km single mode fiber. The module incorporates one channel optical signal, on 1271, 1291, 1311 or 1331nm center wavelength, operating at 100Gbps data rate. This module can convert 4 channels of 25Gbps (NRZ) electrical input data to 1 channel of 100Gbps (PAM4) optical signal, and also can convert 1 channel of 100Gbps (PAM4) optical signal to 4 channels of 25Gbps (NRZ) electrical output data. The electrical interface of the module is compliant with the OIF CEI-28G-VSR and QSFP28 MSA.

Features

- Supports 100Gbps
- 100G Lambda MSA 100G-FR Specification Compliant
- Single 3.3V Power Supply
- Power Dissipation < 4.5W
- Up to 2km over SMF with FEC
- QSFP28 MSA Compliant
- SFF-8636 Rev 2.10a Compliant
- 4x25G Electrical Interface
- LC Duplex Connector
- Commercial Case Temperature Range of 0°C to 70°C
- I²C Interface with Integrated Digital Diagnostic Monitoring
- Safety Certification: TUV/UL/FDA^{*1}
- RoHS Compliant

Applications

- 100G Ethernet
- Data center



Ordering Information

Part No.	Data Rate	Fiber	Distance ^{*3}	Interface	Temp.
EOLQ-161HG-O-02-X6 ^{*2}	100Gbps	SMF	2km	LC	0~+70°C

*1: For the latest certification information, please check with Eoptolink.

*2: Standard version. X refers to CWDM wavelength range 1271nm to 1331nm, please refer to the following table for detailed part number and center wavelength information.

*3: Over SMF.

*The product image is only for reference purpose.

CWDM*⁴ Wavelength

Band	Nomenclature	Part Number	Wavelength(nm)		
			Min.	Typical	Max.
O-band Original	A	EOLQ-161HG-O-02-A6	1264.5	1271	1277.5
	B	EOLQ-161HG-O-02-B6	1284.5	1291	1297.5
	C	EOLQ-161HG-O-02-C6	1304.5	1311	1317.5
	D	EOLQ-161HG-O-02-D6	1324.5	1331	1337.5

*4: 4 Wavelengths from 1271nm to 1331nm, each step 20nm. Please contact Eoptolink to confirm whether the wavelength is available.

Quality

Eoptolink Technology has passed many quality system verifications, established an internationally standardized quality assurance system and strictly implemented standardized management and control in the course of design, development, production, installation and service. For latest certification/accreditation numbers, please, contact us.



Notice

Eoptolink reserves the right to make changes or discontinue any optical link product or service identified in this publication, without notice, in order to improve design and/or performance. Applications that are described herein for any of the optical link products are for illustrative purposes only. Eoptolink makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

Eoptolink Technology Inc., Ltd.

Add: No.127 West Wulian Street, Shuangliu District, Chengdu City 610213, P.R.China.

Tel: +86-028-6708 7983 (HQ); +86-028-6708 7999

Fax: +86-028-6708 7979

Email: sales@eoptolink.com

<http://www.eoptolink.com/>